Feedback for the EVN Users Meeting

Miguel A. Perez-Torres, Antxon Alberdi, Cristina Romero -Cañizales (IAA-CSIC) (torres@iaa.es, antxon@iaa.es, cromero@iaa.es)

- Observations of a sample of ULIRGs (EVN + MERLIN)
- The nuclear region of NGC 7469 (EVN + MERLIN)
- The supernova factory in Arp 299 (eEVN)
- The gamma-ray binary LS I +61 303 (eEVN and MERLIN)

MERLIN should have provided a priori coordinates for the targets, as we required in the proposal. Anyway, MERLIN data were used to know where the target was (more than 5" away in one case!) and be able to obtain EVN images of the targets.

MERLIN should have provided a priori coordinates for the targets, as we required in the proposal. Anyway, MERLIN data were used to know where the target was (more than 5" away in one case!) and be able to obtain EVN images of the targets.

Oct 2006 - RP003 - 5 GHz; CmMcJbOnTrWb. OK. Jb2 used instead of Jb1. MERLIN OK.

MERLIN should have provided a priori coordinates for the targets, as we required in the proposal. Anyway, MERLIN data were used to know where the target was (more than 5" away in one case!) and be able to obtain EVN images of the targets.

Oct 2006 - RP003 - 5 GHz; CmMcJbOnTrWb. OK. Jb2 used instead of Jb1. MERLIN OK.

March 2007 - EA037A - 5 GHz : JbCmWbEfOnMcNtTrShUrHh. Original pipeline didn't include Cm and Wb. Modified after interaction with VLBI friend. MERLIN and EVN antennas OK.

MERLIN should have provided a priori coordinates for the targets, as we required in the proposal. Anyway, MERLIN data were used to know where the target was (more than 5" away in one case!) and be able to obtain EVN images of the targets.

Oct 2006 - RP003 - 5 GHz; CmMcJbOnTrWb. OK. Jb2 used instead of Jb1. MERLIN OK.

March 2007 - EA037A - 5 GHz : JbCmWbEfOnMcNtTrShUrHh. Original pipeline didn't include Cm and Wb. Modified after interaction with VLBI friend. MERLIN and EVN antennas OK.

March 2007 - EB037B - 1.6 GHz: JbCmWbEfOnMcNtTrShUrHh. EVN overall performance OK. MERLIN very bad: Baseline Jb-Cm lost; very bad MERLIN u-v coverage due to complete failure of one antenna. EVN+MERLIN has problems to detect extended emission likely due to the bad u-v coverage of MERLIN.

MERLIN should have provided a priori coordinates for the targets, as we required in the proposal. Anyway, MERLIN data were used to know where the target was (more than 5" away in one case!) and be able to obtain EVN images of the targets.

Oct 2006 - RP003 - 5 GHz; CmMcJbOnTrWb. OK. Jb2 used instead of Jb1. MERLIN OK.

March 2007 - EA037A - 5 GHz : JbCmWbEfOnMcNtTrShUrHh. Original pipeline didn't include Cm and Wb. Modified after interaction with VLBI friend. MERLIN and EVN antennas OK.

March 2007 - EB037B - 1.6 GHz: JbCmWbEfOnMcNtTrShUrHh. EVN overall performance OK. MERLIN very bad: Baseline Jb-Cm lost; very bad MERLIN u-v coverage due to complete failure of one antenna. EVN+MERLIN has problems to detect extended emission likely due to the bad u-v coverage of MERLIN.

MERLIN used different phase-center coordinates for EB037A and EB037B than were used for the EVN, so getting a combined image was a headache.

EPO61A - 1.6 GHz- Essentially all EVN antennas OK. Target (IRAS 2336) imaged with rms close to thermal.

EPO61A - 1.6 GHz- Essentially all EVN antennas OK. Target (IRAS 2336) imaged with rms close to thermal.

EPO61B - 1.6 GHz - Ef: minor falues due to strong winds, Jb1 was offline for entire experiment due to high winds; Nt didn't record for most part of the experiment. This affected the final rms for the images of IRAS 0725- significantly worse than for IRAS 2336 (EPO61A).

EPO61A - 1.6 GHz- Essentially all EVN antennas OK. Target (IRAS 2336) imaged with rms close to thermal.

EPO61B - 1.6 GHz - Ef: minor falues due to strong winds, Jb1 was offline for entire experiment due to high winds; Nt didn't record for most part of the experiment. This affected the final rms for the images of IRAS 0725- significantly worse than for IRAS 2336 (EPO61A).

EPO61C - 5 GHz: Real time system control in Wb died about 1 hr before end. Rest OK. Target imaged with rms close to thermal. Phase jumps in Tr.

EPO61A - 1.6 GHz- Essentially all EVN antennas OK. Target (IRAS 2336) imaged with rms close to thermal.

EPO61B - 1.6 GHz - Ef: minor falues due to strong winds, Jb1 was offline for entire experiment due to high winds; Nt didn't record for most part of the experiment. This affected the final rms for the images of IRAS 0725- significantly worse than for IRAS 2336 (EPO61A).

EPO61C - 5 GHz: Real time system control in Wb died about 1 hr before end. Rest OK. Target imaged with rms close to thermal. Phase jumps in Tr.

EPO61D - 5 GHz: Wb: 2/6 hr lost due to power supply on the real-time control PC failing intermittently. Lovell parked during the whole experiment due to strong winds. Tr uses another frequency southesizer from this eperiment on to try to eliminate the phase jumps.

April 2008 - RP009 - 5 GHz; CmMcJbOnTrWb. OK.

EP061E-H: 1.6 and 5 GHz. Got the data very recently, some problems with pipelined products apparently due to switch of the correlator model to comply with AIPS DEC08. Work under its way, prompt and useful interaction with EVN VLBI friends.



Pipeline the ionosphere correction (TECOR) for EVN data, if it is true that this correction should be done before fringe-fitting (<= 1.6 GHz), as the EVN cookbook claims. This could be done automatically for experiments at all freqs.

Pipeline the ionosphere correction (TECOR) for EVN data, if it is true that this correction should be done before fringe-fitting (<= 1.6 GHz), as the EVN cookbook claims. This could be done automatically for experiments at all freqs.

Overall performance of EVN antennas OK in general, but Cambridge is the "weakest link", yet a very important one for EVN+MERLIN experiments. Its bandwidth is a big limitation; often the Jb-Cm baseline has to be thrown out and then amplitude selfcalibration with the EVN data cannot be done properly.

Pipeline the ionosphere correction (TECOR) for EVN data, if it is true that this correction should be done before fringe-fitting (<= 1.6 GHz), as the EVN cookbook claims. This could be done automatically for experiments at all freqs.

Overall performance of EVN antennas OK in general, but Cambridge is the "weakest link", yet a very important one for EVN+MERLIN experiments. Its bandwidth is a big limitation; often the Jb-Cm baseline has to be thrown out and then amplitude selfcalibration with the EVN data cannot be done properly.

MERLIN performance should be more reliable: phase-center coordinates used by MERLIN should always be the same as for the EVN, if EVN+MERLIN obs-ns; failures of even one antenna has dramatic effects on the u-v coverage and image fidelity. Lack of manpower? Hope this is solved by the time eMERLIN is on.

Pipeline the ionosphere correction (TECOR) for EVN data, if it is true that this correction should be done before fringe-fitting (<= 1.6 GHz), as the EVN cookbook claims. This could be done automatically for experiments at all freqs.

Overall performance of EVN antennas OK in general, but Cambridge is the "weakest link", yet a very important one for EVN+MERLIN experiments. Its bandwidth is a big limitation; often the Jb-Cm baseline has to be thrown out and then amplitude selfcalibration with the EVN data cannot be done properly.

MERLIN performance should be more reliable: phase-center coordinates used by MERLIN should always be the same as for the EVN, if EVN+MERLIN obs-ns; failures of even one antenna has dramatic effects on the u-v coverage and image fidelity. Lack of manpower? Hope this is solved by the time eMERLIN is on.

MERLIN data products could be provided as the EVN does (raw data + tables) by default, or the MERLIN cookbook be more friendly, so as to be able to properly reduce the data.



Wb seems to frequent failures of power supply on the real-time control PC. Shouldn't be difficult to fix this, and given the relevance of the antenna, should be done asap.

- Wb seems to frequent failures of power supply on the real-time control PC. Shouldn't be difficult to fix this, and given the relevance of the antenna, should be done asap.
- RFI at 18 cm is the "usual one". Any ideas to remove most of them?

- Wb seems to frequent failures of power supply on the real-time control PC. Shouldn't be difficult to fix this, and given the relevance of the antenna, should be done asap.
- RFI at 18 cm is the "usual one". Any ideas to remove most of them?
- Chinese antennas getting better and better, and probably are now around, or even above the average EVN antenna performance (leaving apart the three big dishes).

- Wb seems to frequent failures of power supply on the real-time control PC. Shouldn't be difficult to fix this, and given the relevance of the antenna, should be done asap.
- RFI at 18 cm is the "usual one". Any ideas to remove most of them?
- Chinese antennas getting better and better, and probably are now around, or even above the average EVN antenna performance (leaving apart the three big dishes).
- Interaction with VLBI friends, and scheduler (Richard Porcas) useful and prompt. Big thanks to them!

Wb seems to frequent failures of power supply on the real-time control PC. Shouldn't be difficult to fix this, and given the relevance of the antenna, should be done asap.

RFI at 18 cm is the "usual one". Any ideas to remove most of them?

- Chinese antennas getting better and better, and probably are now around, or even above the average EVN antenna performance (leaving apart the three big dishes).
- Interaction with VLBI friends, and scheduler (Richard Porcas) useful and prompt. Big thanks to them!
- Congratulations to Patrick Charlot for his great job as EVN PC Chairman and my best wishes to Tiziana for taking over as chairwoman!